




UGY80YK

UNIVPOWER SILENT SERIES

POWER OUTPUT

Prime Rating — 64 kW (80 kVA)
 Standby Rating — 70.4 kW (88 kVA)
 3-Phase, 50 Hertz, 0.8 PF



STANDARD FEATURES


- Heavy duty, 4-cycle, variable speed fan, diesel engine provides maximum reliability.
- Brushless alternator reduces service and maintenance requirements. Class H protection.
 - Open delta alternator design provides virtually unlimited excitation for maximum motor starting capability.
 - Automatic voltage regulator (AVR) provides precise regulation.
- Electronic governor system maintains frequency to $\pm 0.25\%$.
- Full load acceptance of standby nameplate rating in one step
- Soundproof, weather resistant, steel housing provides operation at 68dB (A) at 7meters. Fully lockable enclosure allows safety operation. Outdoor operation available.
- Internal fuel tank with direct observing glass, and fuel level meter display on control panel
 E-coat and powder coat paint provides durability and weather protection.
- Digital engine gauges including oil pressure, water temperature, battery volts, engine speed, and fuel level.
- Analog generator instrumentation including Ampere meter,
- Voltage meter, frequency meter, ammeter phase selector switch, voltmeter phase selector switch. Analog generator instrumentation and regulator adjustment.
- Deepsea/Comap professional generator controller.
 - High visibility LCD display with heated screen and alphanumeric readout.
 - IP65 Protection standard, operational temperature range of -40° to 85° C.
 - Modbus interface for gauge panel and expansion options.
 - DPF cleaning cycle indication.
 - Log record for inspection
- Automatic safety shutdown system monitors the water temperature, engine oil pressure, low coolant, low DEF, overspeed, and overcrank. Warning lights indicate abnormal conditions.
- Fuel/water separator. Removes condensation from fuel for extended engine life.
- Emergency stop switch — when manually activated, shuts down in any emergency.

UNIVPOWER SILENT SERIES

UNIV POWER DECIBEL LEVELS	
Revolving field, self ventilated weatherproof Normal conversation allows substantially lower operating noise levels than competitive designs. UNIVGensets good for home, construction sites, residential, hospital, etc..	<p>90 — Subway / truck traffic</p> <p>80 — Average city traffic</p> <p>70 — Inside car at 60 mph → UNIVGenset at 7m</p> <p>60 — Air conditioner at 6m</p> <p>50 — Normal conversation</p>

70.0
DECIBELS

GENERATOR OUTPUT PANEL





UGY80YK

UNIVPOWER SILENT SERIES

SPECIFICATIONS

Generator Specifications	
Model	Revolving field, self-ventilated weatherproof
Armature Connection	Star with Neutral
Phase	3
Standby Output	70.4 KW (88 KVA)
Prime Output	64 KW (80 KVA)
Power Factor	0.8
Voltage Regulation (No load to full load)	±0.5%
Generator RPM	1500
Frequency	50 Hz
No. of Poles	4
Excitation	Brushless with AVR
Frequency Regulation: No Load to Full Load	Isochronous under varying loads from no load to 100% rated load
Frequency Regulation: Steady State	±0.25% of mean value for constant loads from no load to full load.
Insulation	Class H
Sound Level dB(A) Full load at 7M	68

Amperage	
Rated Voltage	Maximum Amps
3Ø Volt 230/400	115.5 Amps
3Ø Volt 220/380	121.6 Amps
Main Line Circuit Breaker Rating	160 Amps
Over Current Relay Trip Set Point 400V Mode	176 Amps

Fuel System	
Fuel Tank Capacity	38.3 gallons (145 liters)
Fuel Consumption	L / h
At full load	16.6
At 3/4 load	13.2
At 1/2 load	9.1
At 1/4 load	5.0

Control system	
Controller Brand	SmartGen
Model	HGM420N
Module	Manual/Auto start/stop module
Standard function	Engine control
	Generator monitoring
	Generator protection
	Specification
Display	Frequency
	Battery voltage
	Running hour
Warning/shutdown	under/over voltage
	under/over speed
	under/over frequency
	Low oil pressure
	High water temperature
Communication port	USB

Engine Specifications	
Make / Model	YUNNEI/ YN48GBZ
Emissions	/
Starting System	Electrical start
Design	4 cylinder, 4-cycle, water cooled, direct injection, Turcharged innercooled
Displacement	4.8Liters
No. cylinders	4
Bore x Stroke	108*132mm
Gross Engine Power Output	98 hp (72 kW)
Compression Ratio	18:1
Engine Speed	1500 rpm
Overspeed Limit	1570 rpm
Oil Capacity	1.85gallons (7liters)
Coolant Capacity	4.76 gallons (18 liters)
Battery	12V 60Ah x 1

Alternator	
Alternator Brand	KWISE
Alternator Model	S224G64D8
Excitation	Brushless, Self-Excited system
Capacity(KVA)	80 kva
Power(KW)	64 kw
Efficiency(%)	88.9%
Insulation class	Class H
Protection class	Ip23
Steady state voltage regulation	±1%
Voltage control	AVR

WARRANTY*

Generator

12 months from date of purchase or 1000 running hours (whichever occurs first)



NOTICE

Enough Air flow is extremely important to Generator operation. Improper connection can cause electrocution and/or property damage. Do not connect to any electrical system except through an approved device. Specifications are subject to change without notice.




UGY80YK

UNIVPOWER SILENT SERIES



Weight	
Dry Weight	1,600 kg
Wet Weight	1,740 kg
Max. Lifting Point Capacity	4,000 kg



Manufactured by
Zhejiang Universal Machinery Co., Ltd
Add: No 18-9 Nanshan Road, Qujiang Zone,
Quzhou city, Zhejiang Province, CN
Tel: 0086-570-3377022
Fax: 0086-570-3377023
Website: www.univpower.com